

SV 80

General Purpose Vibration Accelerometer



INSTRUMENTATION FOR SOUND & VIBRATION MEASUREMENTS

The SV 80 is an industry standard IEPE piezoelectric accelerometer offered to Svantek's Vibration Level Meters (974, 977A, 979, 958A).

It is an ideal choice for walk-around vibrations measurement in the rugged environments of **INDUSTRIAL** machinery monitoring, such as pumps, motors etc.

The accelerometer is mounted on a vibrating surfaces with the mounting magnet.



Optional accessories to SV 80



SV 110
Hand-held
Vibration Calibrator



SA 27
Mounting Magnet



SC 27
TNC/TNC coil cable

SV 80 Technical Specifications

Performance

Number of Axes	1
Sensitivity ($\pm 5\%$)	10 mV/(m/s ²) ~ 100 mV/g
Measurement Range	0.01 m/s ² RMS \div 500 m/s ² Peak
Frequency Response (by design guideline, ± 3 dB)	0.5 Hz \div 14 000 Hz
Resonant Frequency	25 kHz
Residual Noise (1 Hz, 24°C)	30 μ g RMS
Residual Noise (1 Hz to 25 kHz, 24°C)	300 μ g RMS

Electrical

Supply Current (IEPE)	2 mA \div 10 mA
Supply Voltage (IEPE)	22 V \div 28 V
Bias Voltage (IEPE)	+12 VDC
Output Impedance (Nominal)	50 Ω
Charge / Discharge Time Constant (start-up time)	< 1 sec. typ.

Environmental Conditions

Maximum Vibration (shock survival)	50 000 m/s ² Peak
Thermal Sensitivity Coefficient	0.07 %/°C F.S.
Operating Temperature Range (recommended)	from -10 °C to +50 °C
Humidity / Enclosure	IP 67, epoxy sealed

Physical

Connector	TNC socket, top radially mounted
Weight	40 grams
Mounting Thread	10-32 UNF 2B

Proudly distributed by:

SVANTEK Sp. z o. o.
ul. Strzygłowska 81, 04-872 WARSAW, POLAND
phone/fax (+48) 22 51 88 320, (+48) 22 51 88 312
<http://www.svantek.com> e-mail: office@svantek.com.pl